


RCCN 日成BGQF型快速软管防水接头 Water Conduit Connector



螺母 LockNut A 垫片 Washer B 本体 Body C 夹紧圈 Seal D 迫紧头 SealingNut F 日成软管 Connector G

螺牙规格:公制螺牙(Metric),德制螺牙(DIN STANDARD)。
 产品材质:A.C.F部位均采用环保尼龙66(NYLON66)原料制成.B.D采用耐老化橡胶材质。
 产品认证:欧洲CE,ROHS, 欧洲环保SGS。
 防火等级:UL94V-2。
 工作温度:-40°C至150°C。
 防护等级:在规定的卡口范围内,并使用O形密封圈旋紧迫紧头,达到IP68。
 颜色种类:浅灰色、黑色,特殊颜色如灰/红/蓝均可订做。
 使用方法:先将本体穿于机板,再以螺母扭紧固定,软管穿过迫紧头套进夹紧圈到底,扭紧迫紧头将其固定。

另备灰色,例: BGQF-M12G (BG-07)

Thread:Metric,DIN STANDARD
 Material:A.C.F parts made of NYLON66,B.D parts made of rubber
 Certificates:CE,ROHS,SGS。
 Fireproof rate:UL94V-2。
 Work temperature:-40°C to 150°C。
 Protect rate:in bayonet scope,usd with O ring,screw down lock nut,can be up to IP68
 Colors:light gray,black,other special colors can be made
 How to use:input it to panels,fixed with lock nut,insert conduit to sealing nut,screw down the nut。
 Gray is available in stock : BGQF-M12G (BG-07)

单位/Unit:mm

型号 Item No.	螺纹规格	对应日成软管型号 Suit to RCCN conduit item no	对应日成软管型号 Suit to RCCN conduit item no	螺纹外径 Thread O.D.	机板开孔 Panel Mounting Hole	螺纹长度 Thread Length	包装 Std.Pkg. pcs	
黑色Black	Thread	BG	BG	D1		L1		
公制螺纹 /Metric thread BGQF-M								
BGQF-M12B(BG-07)	M12×1.5	BG-07	10.0	12	12-12.3	8.5	100PCS	
BGQF-M16B(BG-10)	M16×1.5	BG-10	13.0	16	16-16.3	10		
BGQF-M16B(BG-12)	M16×1.5	BG-12	15.8	16	16-16.3	10		
BGQF-M16B(BG-15)	M16×1.5	BG-15	18.5	16	16-16.3	10		
BGQF-M20B(BG-12)	M20×1.5	BG-12	15.8	20	20-20.3	10		
BGQF-M20B(BG-15)	M20×1.5	BG-15	18.5	20	20-20.3	10		
BGQF-M20B(BG-17)	M20×1.5	BG-17	21.2	20	20-20.3	10	20PCS	
BGQF-M25B(BG-23)	M25×1.5	BG-23	28.5	25	25-25.4	12		
BGQF-M32B(BG-23)	M32×1.5	BG-23	28.5	32	32-32.4	12		
BGQF-M32B(BG-29)	M32×1.5	BG-29	34.5	32	32-32.4	12		
BGQF-M40B(BG-36)	M40×1.5	BG-36	42.5	40	40-40.4	12		
BGQF-M50B(BG-48)	M50×1.5	BG-48	54.5	50	50-50.4	15		
BGQF-M63B(BG-48)	M63×1.5	BG-48	54.5	63	63-63.4	20	100PCS	
德制螺纹 Germany thread BGQF-P								
BGQF-PG7B(BG-07)	PG7	BG-07	10.0	12.5	12.5-12.8	10		
BGQF-PG9B(BG-07)	PG9	BG-07	10.0	12.5	15.2-15.5	10		
BGQF-PG9B(BG-10)	PG9	BG-10	13.0	12.5	15.2-15.5	10		
BGQF-PG11B(BG-10)	PG11	BG-10	13.0	18.6	18.6-18.9	10		
BGQF-PG11B(BG-12)	PG11	BG-12	15.8	15.2	18.6-18.9	10		
BGQF-PG11B(BG-15.8)	PG11	BG-12	18.5	15.2	18.6-18.9	10		
BGQF-PG13.5B(BG-12)	PG13.5	BG-12	15.8	20.4	20.4-20.7	10		
BGQF-PG13.5B(BG-15)	PG13.5	BG-15	18.5	20.4	20.4-20.7	10		
BGQF-PG16B(BG-12)	PG16	BG-12	15.8	22.5	22.5-22.8	11		
BGQF-PG16B(BG-15)	PG16	BG-15	18.5	22.5	22.5-22.8	11		
BGQF-PG16B(BG-17)	PG16	BG-17	21.2	22.5	22.5-22.8	11		
BGQF-PG21B(BG-23)	PG21	BG-23	28.5	28.3	28.3-28.7	12.5		
BGQF-PG29B(BG-29)	PG29	BG-29	34.5	37.0	37.0-37.4	13		
BGQF-PG36B(BG-36)	PG36	BG-36	42.5	47.0	47.0-47.4	13		
BGQF-PG48B(BG-48)	PG48	BG-48	54.5	59.3	59.3-54.7	16		